

# GOODYEAR G572A LHD

## Drive Tire Specifications & Features



Fuel-saving compounds help promote energy efficiency as the tire rolls to enhance fuel economy



Deep 30/32" tread depth provides enhanced wearable rubber for long tire life



Tredlock Technology features interlocking microgrooves that help stabilize the tread for long tread life and enhanced toughness



TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	134	61	8.25	11.0	279	42.4	1,077	19.9	505	492	306	30	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	134	61	8.25	11.0	279	42.4	1,077	19.9	505	492	306	30	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	130	59	8.25	11.3	287	41.1	1,044	19.3	490	508	316	30	12.9	328	75
11R24.5	G	6,160	3,000	105	720	6,005	2,725	105	720	143	65	8.25	11.0	279	44.4	1,028	20.8	528	470	292	30	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.0	279	44.4	1,028	20.8	528	470	292	30	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	140	64	8.25	11.0	279	42.2	1,072	19.7	500	495	308	30	12.5	318	75

# DUNLOP SP 456

## Drive Tire Specifications & Features



Featuring fuel-saving compounds to promote energy efficiency as the tire rolls to enhance fuel economy



Four-belt construction enhances toughness and lengthens tire life



Circumferential and lateral grooves to help deliver all-season traction



TIRE SIZE	TREAD DEPTH	RIM WIDTH		TIRE WEIGHT		OVERALL WIDTH		OVERALL DIAMETER		STATIC LOAD RADIUS		SPEED RATING	SINGLE MAX LOAD		SINGLE INFLATION		DUAL MAX LOAD		DUAL INFLATION		REVS PER		MIN. DUAL SPACING	
		in	mm	lbs	kg	in	mm	in	mm	in	mm		mph	lbs	kg	psi	kpa	lbs	kg	psi	kpa	mi	km	in
<b>11R22.5G</b>	26	8.5	210	125	57	10.9	277	41.9	1,064	19.5	495	75	6,175	2,800	105	720	5,840	2,650	105	720	498	310	12.5	318
<b>285/75R24.5G</b>	26	8.25	210	124	56	10.8	274	42.3	1,074	19.8	503	75	6,610	3,000	110	760	5,675	2,575	110	760	493	306	12.5	318
<b>295.75R22.5G</b>	26	8.25	210	124	54	11.1	282	41.1	1,044	19.2	488	0	6,175	2,800	110	760	5,675	2,575	110	760	508	316	12.9	328