

# GOODYEAR G399A LHS

## Steer Tire Specifications & Features



Innovative fuel-saving compounds lower rolling resistance to help enhance fuel economy, while maintaining long mileage



Outside tread shoulder compound helps protect the pressure distribution groove from tearing, which promotes even wear



Four-belt construction enhances toughness & lengthens tire life



TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH			OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg		in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>11R22.5</b>	G	6,175	2,800	105	720	5,840	2,650	105	720	113	51	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75	
<b>11R22.5</b>	H	6,610	3,000	120	830	6,005	2,725	120	830	113	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75	
<b>295/75R22.5</b>	G	6,175	2,800	110	760	5,675	2,575	110	760	109	50	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.9	328	75	
<b>295/75R22.5</b>	H	7,160	3,250	123	850	6,610	3,000	123	850	110	50	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.9	328	75	
<b>11R24.5</b>	G	6,160	3,000	105	720	6,005	2,725	105	720	122	55	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75	
<b>22R24.5</b>	H	7,160	3,250	120	830	6,610	3,000	120	830	122	56	8.25	10.8	274	43.2	1,097	20.1	411	481	299	18	12.5	318	75	
<b>285/75R24.5</b>	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75	
<b>285/75R24.5</b>	H	6,780	3,075	120	830	6,175	2,800	120	830	114	52	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75	



(866) 472-1120 | [www.qualityco.com/tire-discount/](http://www.qualityco.com/tire-discount/)

# DUNLOP SP 384

## Steer Tire Specifications & Features



Featuring fuel-saving compounds to help promote energy efficiency as the tire rolls to enhance fuel economy



Five-rib construction and pressure distribution groove help promote even wear for long tire life



Lateral grooves and rib-edge sipes enhance traction in wet, icy and snowy conditions



TIRE SIZE	TREAD DEPTH	TIRE WEIGHT		SINGLE MAX LOAD		SINGLE INFLATION		DUAL MAX LOAD		DUAL INFLATION	
		lbs	kg	lbs	kg	psi	kpa	lbs	kg	psi	kpa
<b>11R22.5G</b>	18	116	52	6,175	2,800	105	720	5,840	2,650	105	720
<b>11R22.5H</b>	18	120	54	6,610	3,000	120	830	6,005	2,725	120	830
<b>11R24.5G</b>	18	125	57	6,610	3,000	105	720	6,005	2,725	105	720
<b>11R24.5H</b>	18	128	58	7,160	3,250	120	830	6,610	3,000	120	830
<b>285/75R24.5G</b>	18	117	53	6,175	2,800	110	760	5,675	2,575	110	760
<b>295/75R22.5G</b>	18	111	50	6,175	2,800	110	760	5,675	2,575	110	760