

GOODYEAR G3 16 LHT

Trailer Tire Specifications & Features



Fuel-saving compounds help promote energy efficiency as the tire rolls to enhance fuel economy



Protective shoulder compound helps guard the outer tread from accidental curb damage



Innovative sealant built into the tire seals tread punctures to help keep trucks up-and-running, as well as reduce repair and replacement costs



TIRE SIZE	TREAD DEPTH	RIM WIDTH		TIRE WEIGHT		OVERALL WIDTH		OVERALL DIAMETER		STATIC LOAD RADIUS		SPEED RATING	SINGLE MAX LOAD		SINGLE INFLATION		DUAL MAX LOAD		DUAL INFLATION		REVS PER		MIN. DUAL SPACING	
		in	mm	lbs	kg	in	mm	in	mm	in	mm		mph	lbs	kg	psi	kpa	lbs	kg	psi	kpa	mi	km	in
11R22.5G	12	8.5	210	106	48	10.9	277	41.0	1,041	19.0	483	75	6,175	2,800	105	720	5,840	2,650	105	720	483	300	12.5	318
11R24.5G	12	8.25	210	108	49	11.2	284	43.1	1,095	20.1	511	75	6,610	3,000	105	720	6,005	2,725	105	720	478	297	12.5	318
255/70R22.5H	13	7.50	191	87	39	10.1	257	36.3	922	17.1	434	81	5,510	2,800	120	830	5,070	2,300	120	830	568	353	11.3	287
275/70R22.5J	14	7.50	191	96	44	10.5	267	37.5	953	17.5	445	75	6,940	2,900	130	900	6,395	2,900	130	900	550	342	11.9	302
285/75R24.5G	12	8.25	210	108	49	11.1	282	41.0	1,041	19.1	484	75	6,175	2,800	110	760	5,675	2,575	110	760	503	313	12.5	318
295/75R22.5G	12	8.25	210	102	46	11.1	282	39.8	1,011	18.6	472	75	6,175	2,800	110	760	5,675	2,575	110	760	518	322	12.9	328

DUNLOP SP 193

Trailer Tire Specifications & Features



Featuring fuel-saving compounds to promote energy efficiency as the tire rolls to enhance fuel economy



Four-belt construction enhances toughness and lengthens tire life



Protective shoulder compound to help guard the outer tread from any accidental curb damage



TIRE SIZE	TREAD DEPTH	RIM WIDTH		TIRE WEIGHT		OVERALL WIDTH		OVERALL DIAMETER		STATIC LOAD RADIUS		SPEED RATING	SINGLE MAX LOAD		SINGLE INFLATION		DUAL MAX LOAD		DUAL INFLATION		REVS PER		MIN. DUAL SPACING	
		in	mm	lbs	kg	in	mm	in	mm	in	mm		mph	lbs	kg	psi	kpa	lbs	kg	psi	kpa	mi	km	in
11R22.5G	12	8.5	210	100	46	11.1	282	41.1	1,044	19.1	485	75	6,175	2,800	105	720	5,840	2,650	105	720	502	312	12.5	318
11R24.5G	12	8.25	210	106	48	10.8	274	43.1	1,095	20.3	516	75	6,610	3,000	105	720	6,005	2,725	105	720	478	297	12.5	318
285/75R24.5G	12	8.25	210	101	46	11.1	282	40.9	1,039	19.2	488	75	6,175	2,800	110	760	5,675	2,575	110	760	504	313	12.5	318
295/75R22.5G	12	8.25	210	98	45	11.2	284	39.9	1,013	18.6	472	75	6,175	2,800	110	760	5,675	2,575	110	760	517	321	12.5	328